



## **DCA12.0**

REMIUM QUALITY Cleaning Applicator

IGH QUALITY Cleaning Applicator

## **CLEANING APPLICATORS**

ANEST IWATA Spray Cleaning Applicators High Quality Atomizers are especially suited for applications in the automotive industry, motorcycle and bicycle garages, in the machine and metalworking industries, workshops, home and garden.

- Special adjustable nozzle ø 0.8 mm
- · Powerful nickel plated brass piston pump giving up to 12 bar pressure
- · Robust tank 1 litre, transparent with Iling level indicator, measuring scale and easy grip
- · Large Iling opening
- · Ergonomically shaped handle for easy operation
- · Good stability due to large tank design

## PCA12.0 with Super Seal BMS 210

MAXIMUM RESISTANCE TO AGGRESSIVE SOLVENTS

· Solvents resistant special gaskets (BMS 210)

## HCA12.0 with Viton Seal FPM .

HIGH RESISTANCE TO STANDARD SOLVENTS



Models	PCA12.0	HCA12.0
Chemical Resistance	Especially suitable for mineral oil resp. petroleum based products, which contain also Acetone (or similar solvents) and/or Alcohol	Suitable for mineral oil based products, solvents, separating agents, wax products, emulsions and higher viscosity products. Not suitable for acetone containing products
Tank material	PE transparent white	
Gaskets	Special Gaskets BMS 210	Viton FPM
Pump	Nickel plated brass	
Type of nozzle	Nickel plated brass adjustable nozzle 0.8 mm	
Weight (empty)	310 g	
Tank capacity	1 litre	
Dimensions	H250 mm, Ø 120 mm	
Max. operating pressure	12 bar	
Temperature range	from 5° to 50° C	



Special adjustable nozzle Ø 0.8 mm.

Special solvent resistant gaskets (BMS 2010).

Powerful nickel plated brass piston pump giving up to 12 bar pressure. Pump easy to dismantle.